

# INTRODUCING THE NEXT GENERATION OF REAL-TIME STORM DETECTION

ARM-BASED 3 MICROPROCESSOR ARCHITECTURE FOR HIGH RESOLUTION  
DIRECT - TO - DIGITAL DATA COLLECTION

## NIMBUS™4 NIMBUS™4D

Powered By **NIMBUS™** Technology

### GET YOURS BEFORE THE STORM!™

#### PRIMARY DETECTION FUNCTIONS

- Storm detection range 600 miles (966 KM)
- Early Storm Formation Alerts out to 20 miles
- Squall line detection • Pre-tornado conditions



#### 4 ANTENNA ARRAY

- Cloud to Ground • Cloud to Cloud
- Positive Polarity Strokes



In Charge Base

LED DISPLAY - Red, Yellow, Blue

BACK-LIT 128 x 64 MONOCHROME GRAPHIC DISPLAY

#### 4 LANGUAGE DISPLAY OPTIONS

NIMBUS™4 will arrive with four pre-programmed languages (English, French, Spanish and Portuguese) to choose from and many more available for download from the NIMBUS4.com website.

#### REAL-TIME CLOCK

Allows for modification to calibration based on time-of-day and day-of-year

#### ACTIVE DATA REGISTER

- 10,000 data points for storms
- 20,000 data points for squall line and hurricane conditions

#### DATA LOGGING

- Able to store up to one year of operating activity internally without any download
- Provides the enthusiast, storm chaser or meteorologist the ability to study storm pattern and activity during different times of the year

#### USB PORT

- Field diagnostics & calibration
- Cloud-based networking of up to 10 units
- Download of up to one year of stored data

#### SOFTWARE ADJUSTMENTS

For latitude and terrain



#### DIMENSIONS:

7 x 4 x 1.5 inches

WEIGHT: 1 LB

3200 mAh RECHARGEABLE LITHIUM-ION BATTERY

The **NIMBUS™4D** combines the un-paralleled storm detection capabilities of the **NIMBUS™4** with Entropy's patent-pending directional system. Using the high-resolution storm data collected by the 4-channel antenna array, the **NIMBUS™4D** software provides the bearing to storm activity in 30 degree segments. Just as with all storm information provided by the **NIMBUS™** technology, the storm direction is based on real-time data processed at the exact location of the **NIMBUS™** unit.

The **NIMBUS™4D** display uses an on-board compass module to display the bearing to storm activity relative to true North. The storm bearing information is updated in real-time using the storm data being collected by the unit.

ENTROPY TECHNOLOGY DESIGN, INC.

10006 Cross Creek Blvd., Suite 415 Tampa, FL 33647

www.entropydesigns.com www.nimbus4.com Contact: info@nimbus4.com or info@entropydesigns.com